

# FS-1900N Specifications

## BASIC SPECIFICATIONS:

Configuration:	Desktop Network Monochrome Printer with Standard 500 Drawer plus 100 Sheet Multi-Purpose Tray
Resolution:	Fast 1200 dpi (1800 x 600), 600 x 600 dpi, 2400 x 600 dpi (w/KIR)
Printer Memory:	Standard 16MB, upgradable to 144MB via 100 pin DIMMs; Standard CF Card Slot (Type 1), Micro Drive Slot (up to 1GB)
Electrical Requirements:	120V, 60Hz, 7.2A
Dimensions:	13.6"W x 11.8"H x 18.1"D
Weight:	28.7 lbs
Max Duty Cycle:	65,000 Pages

## CONTROLLER SPECIFICATIONS:

Controller:	PowerPC405 200 MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL5e), KPDL2 (PS2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e and KPDL2, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell Netware™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Connectivity / Interface:	Standard IB-21e 10/100BaseTX, Parallel IEEE1284, Full-Speed USB 2.0
KUIO LV Expansion Slots (1):	Optional IB-11 Serial RS-232C; IB-20 10/100BaseTX, 10Base2; IB-22 Enhanced Wireless NIC
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

## OUTPUT SPEEDS:

Warm-Up Time:	Less than 16 Seconds
First Print Out:	Less than 9.5 Seconds
Pages Per Minute:	19 Letter, 15 Legal

## PAPER SUPPLY:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", A4, B5, A5
MPT Paper Size:	8.5" x 11", 8.5" x 14", A4, B5, A5 Custom (2.8" x 5.8" - 8.5" x 11.7")
Std/Max Paper Capacity:	600 Sheets/2600 Sheets
Paper Weight:	16-28 lb Bond via Paper Drawer, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

## PAPER HANDLING OPTIONS:

### DUPLEX UNIT: DU-60

Paper Size:	8.5" x 11", A4, B5, A5
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 20.5"D x 4.2"H/10.1 lbs

### PAPER DRAWER: PF-60

Paper Capacity:	500 Sheets
Max. Drawers:	3
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4, B5, A5
Dimensions / Weight:	13.6"W x 17.8"D x 4.1"H/8.4 lbs

### PAPER FEEDER: PF-8E

Paper Capacity:	2,000 Sheets
Max. Drawers:	1
Paper Weight:	16 lb Bond- 110 lb Index
Paper Size:	8.5" x 11", A4, B5, A5
Dimensions / Weight:	13.6"W x 14.8"D x 13.9"H/16.6 lbs

### BULK STACKER: HS-8E

Stack Capacity:	2,000 Sheets
Paper Weight:	16 lb Bond- 110 lb Index
Paper Size:	8.5" x 11", A4, B5, A5
Dimensions / Weight:	13.6"W x 13.1"D x 14.7"H/15.9 lbs

### 5-BIN MAILBOX: SO-60

Number of Trays:	5
Mailbox Capacity:	200 Sheets: 8.5" x 11", A4, B5, A5; 100 Sheets: 8.5" x 14"
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 6.7"D x 12.4"H/11.7lbs

## ADDITIONAL OPTIONS:

Envelope Feeder (EF-60), Face-Up Tray (FT-200), Face-up Tray for DU-60 (PT-60), Base for PF-8E/HS-8E (PB-60), Legal Tray for PF-60 (PC-60 LGL), Letter Tray for PF-60 (PC-60 LTR)

## CONSUMABLES:

TK-50:	10,000 pages @ 5% Coverage
	* Ships with 5,000 pages @ 5% Coverage



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.  
225 Sand Road, PO Box 40008,  
Fairfield, NJ 07004-0008, USA  
©2003 Kyocera Mita America, Inc.  
[www.kyoceramita.com](http://www.kyoceramita.com)



Printed on Recycled Paper with 50% Recycled Content