

KM-3650w Specifications

BASIC SPECIFICATIONS:

Configuration:	Wide Format MFP with Standard Network Printing and Scanning. Standard with two 500' Paper Rolls, Single Sheet Bypass. Standard 512MB RAM, 80GB HDD. Optional Enhancement Kit.
Technology:	LED
Resolution:	600 x 600 dpi
Original Memory:	Standard 512MB RAM, 80GB HDD
Magnification:	Full Size, 3 Reduction, 5 Enlargement Preset Ratios, 25-400% Zoom in 0.1% steps, XY Zoom
Electrical Requirements:	120V, 60Hz, 15A
Dimensions:	58.5"W x 29.4"D x 49.4"H
Weight:	479 lbs

OUTPUT SPEEDS:

Warm-Up Time:	Within 5 Minutes, Auto Start
First Print Out (D Size):	Within 24 Seconds
First Copy Out (D Size):	Within 40 Seconds
Pages Per Minute:	11.8' per minute 4 D Size copies/prints per minute

PAPER SUPPLY:

Standard Paper Sources:	2 Rolls (Max. Capacity 500' per roll), Single Sheet Bypass
Min/Max Roll Width:	11"/36"
Min/Max Bypass Paper Size:	8.5" x 11"/36" x 48"
Paper Weight:	16-20 lbs
Media Type:	Bond Paper, Film, Translucent Bond, Vellum

DOCUMENT SCANNER:

Scanning Direction:	Face-up Scanning
Scanning Resolution:	600 x 600 dpi
Acceptable Originals:	Width: 8.5" to 36", Length: 11" to 472"
Capacity:	Single Sheet
Standard Drawing Sizes:	Architectural/ANSI/Metric

OUTPUT:

Output Width:	8.5" - 36"
Output Length:	11" - 472"
Standard Drawing Sizes:	Architectural/ANSI/Metric
Output Tray Capacity:	Up to 10 E Size

COPY FUNCTIONS:

Imaging Modes:	Line, Grayscale, Line/Grayscale
Continuous Copy:	Up to 99
Additional Copy Features:	Auto Center, Auto Magnification, Auto Paper Select, Rotate Image, Margin Shift, Border Erase, Mirror Image, Interrupt, Repeat Copy, Sort/Group, Date Stamp, Background Removal, Add Job

CONNECTIVITY:

Standard Network Controller

BASIC SPECIFICATIONS:

Platform:	Linux
Controller:	Duron CPU/2.66GHz
Printer Memory:	Standard 512MB RAM, 80GB HDD (Shared)
Connectivity:	Standard 10/100 Base TX

NETWORK PRINT:

Standard File Formats:	HP-GL, HP-GL/2, HP-RTL, Calcomp 906/907, CALS-G4 (TIFF 6.0), TIFF, BMP, JPEG, DXF
Optional File Formats:	PDF, PostScript (requires UG-32 Option)
Windows® OS Compatibility:	Windows® 2000/XP/Vista
Supported Protocols:	TCP/IP
Drivers:	Windows Print Driver, HDI for AutoCAD®, PostScript Driver
HDI Driver Compatibility:	AutoCad® 2000/2000i/2002/2004/2005/2006/2007/2008
Utilities:	Remote Web Manager, WF Print Client
Print Option:	UG-32 Enhancement Kit

NETWORK SCAN:

Resolution:	100, 200, 300, 400, 600
Scan Speed:	Up to 4 D's/minute
Scan Modes:	Line, Grayscale, Line/Grayscale
File Formats:	TIFF(G3/G4), CALS-G4, JPEG, BMP, PDF
Connectivity:	Standard 10/100 Base TX
Supported Protocols:	TCP/IP
Scanning Modes:	Scan to PC/File, Scan to FTP, Web Scanning
Additional Scan Features:	Continuous Scan, Background Removal, Border Erase, Mirror Image, Simultaneous Scan & Copy
Utilities:	Remote Web Manager



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.
Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2007 Kyocera Mita America, Inc.



www.kyoceramita.com