

# CS-2540 Specifications

## Basic Specifications:

Configuration:	Workgroup Multifunctional with Standard Copy and Optional Print and Optional Fax. Standard 500 x 2 Paper Drawers Plus 200 Sheet Multi-Purpose Tray. Standard Duplex. Optional Document Processor. Optional Finishing and Paper Handling.
Resolution:	600 x 600 dpi / 256 Levels, Fast 1200 Print Mode
Copier Memory:	Standard 64MB RAM, Upgradeable to 192MB
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom
Electrical Requirements:	120V, 60Hz, 9A
Dimensions:	22.4"W x 25.2"D x 30.2"H
Weight:	166 lbs
Max Monthly Volume:	80,000 Pages Per Month

## Output Speeds:

Warm-Up Time:	Within 15 Seconds, Program During Warmup, Auto Start
First Copy Out / First Print Out:	4.7 Seconds
Pages Per Minute:	25 Letter, 12.5 Legal, 12.5 Ledger

## Paper Supply:

Standard Paper Sources:	Dual 500 Sheet Drawers, 200 Sheet MPT, Auto Tray Selection / Switching, Add Paper While Running
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	1,200 / 2,200
Paper Weight:	16 - 32 lb Bond via Paper Drawers, 12 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

## Duplex Unit:

Duplex Type:	Standard Embedded Stackless
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17 - 21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

## Copy Functions:

Control Panel:	Touch Screen Interface
Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Interrupt Copy, Repeat Copy, Scan Once Print Many, Electronic Sort, Rotate Sort, 2 in 1, 4 in 1, Border Erase, Margin Shift, Continuous Scan, Eco Mode

## Paper Handling Options:

### Document Processor: DP-670

Type:	Reversing Automatic Document Processor (RADF)
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Processing
Capacity:	75 Sheet RADF / 30 Letter Size Originals Per Minute
Paper Weight:	12 - 43 lb Bond
Dimensions / Weight:	22.1"W x 19.2"D x 5.0"H / 15.4 lbs

### Finisher: DF-730

Stack Capacity:	1,000 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	12 - 43 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	Single Position
Dimensions / Weight:	21.9"W x 20.7"D x 36.0"H / 55 lb

### Internal Finisher: DF-670

Stack Capacity:	500 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 32 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	Single Position
Dimensions / Weight:	12.8"W x 17.8"D x 6.5"H / 17.7 lbs

### Dual Paper Drawers: PF-670

Paper Capacity:	500 x 2 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	22.4"W x 24.4"D x 12.2"H / 55.2 lbs

## Connectivity:

### Optional Network Print: PRINT SYSTEM (Y)

Controller:	Embedded PowerPC750/ 400 MHz Controller
Printer Memory:	Standard 64MB, Upgradeable to 576MB, Optional HDD, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003/Vista
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, High Speed USB 2.0
KUIO LV Expansion Slot (2):	IB-23 Secure NIC; Optional Printer HDD
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Drivers:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers
Utilities:	KMnet Admin, KM-NET Viewer, KM-NET for Clients, KM-NET for Accounting, PDF Direct Print
Web Interface:	Kyocera Command Center

### Optional Fax: FAX SYSTEM (P)

Compatibility:	Super G3
Quick Scan Speed:	1.2 SPP
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Standard 4MB / Maximum 32MB
Additional Fax Features:	Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting

## Additional Options:

Job Separator (JS-670); Attachment Kit (AK-670); 32MB Fax Memory; 128MB Copier Memory; 512MB Printer Memory; Stand