

KM-F650 Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Fax with 33.6Kbps Modem and 250 Sheet Cassette, plus Standard Copying, Printing and Scanning Functions		
Compatibility:	ITU-T Group 3		
Scanning Resolution:	Standard:	203 dpi x 96 lpi	
	Fine:	203 dpi x 196 lpi	
	Super Fine:	203 dpi x 391 lpi	
		406 dpi x 392 lpi (interpolated)	
Print Resolution	Fax/Copy:	406 dpi x 391 lpi	
	Print:	600 dpi x 600 dpi	
Fax Memory:	Standard 2MB, Upgradeable to 10MB - Flash Memory		
Memory Capacity:	Std 120 pages/Max 760 pages		
Document Memory Backup:	Std Flash Memory		
Coding System:	MH/MR/MMR		
Scanning Method:	CCD		
Print Method:	Laser		
Max Print Width:	8.2"		
Electrical Requirements:	108 - 132V, 47 - 63Hz		
Dimensions:	14.6"W x 18.5"D x 9.9"H		
Weight:	19.8 lbs		

SPEEDS:

Modem Speed:	33.6Kbps - 2.4Kbps with Automatic Fallback		
Transmission Speed:	3 spp Super G3		
Pages Per Minute:	6.5 Letter Copy & Print		

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer		
Drawer Paper Size:	8.5" x 11"/8.5" x 14"		
Std/Max Paper Capacity:	250/500		
Paper Weight:	16-20 lb Bond		

DOCUMENT PROCESSOR:

Type:	ADF		
Acceptable Originals:	5.8" x 5" - 10.1" x 78.77"		
Capacity:	50 Sheet		
Paper Weight:	12 - 24 lb Bond		
Effective Scanning Width:	8.3"		
Quick Scan:	2.8 spp		

FAX FUNCTION:

DIALING CAPABILITIES:

One-Touch Dialing Keys:	28		
Program/One-Touch Keys:	4		
Speed-dialing Codes:	100		
Max. Numbers Stored:	132		
Redial Attempts/Intervals:	Up to 5/1 to 15 minutes		
Group Dialing:	4 Groups/131 numbers		
Other Dialing:	Chain Dialing, Directory Search Dialing, Pulse/Tone Dialing		
Max. Dialing Digits:	36		

ADDITIONAL FEATURES:

Transmission/Reception: Multi Access, Memory Transmission, Quick Memory Transmission, Delayed Transmission (10 timers), ECM, Auto Fax/Tel. Switch, Polling (144 Locations), Memory polling, Continuous Polling, Verification Stamp, Broadcast Transmission (144 locations), Distinctive Ring Detection (DRD), Memory Reception, Delayed Polling, Delayed Multi-Station Polling (10 timers/144 locations), Substitute Reception, Auto Reduction

Security Communication/Codes: Confidential Transmission/Reception (10 mailboxes), Password Communication, Access Codes

Journals and Lists: Transaction Journal, Communication Journal, One Touch List, Abbreviated Number List, Program List

UTILITIES:

Configuration Editor and Phonebook editor

PRINT:

Std/Max Memory:	5MB/5MB DRAM	
Windows™ OS Compatibility:	Windows 98/Me/NT4.x/2000/XP	
Connectivity :	Standard Parallel IEEE 1284	
Driver:	Windows GDI	
Utilities:	Status Monitor	

SCAN:

Resolution:	400 x 400 dpi	
File Format:	PDF, TIFF, JPEG, Bitmap	
Connectivity:	Standard Parallel IEEE 1284	
Scanning Type:	PC Scanning	
Driver:	TWAIN	
Utilities:	Standard Document Management Software	

COPIY:

Continuous Copy:	Up to 99	
Zoom:	70% to 100%	

PAPER HANDLING OPTIONS:

PAPER DRAWER: PF-40

Paper Capacity:	250 Sheets	
Paper Weight:	16 - 24 lb Bond	
Paper Size:	8.5" x 11", 8.5" x 14", A4	
Dimensions/Weight:	13.7"W x 16.9"D x 3.2"H/5.5 lbs	

ADDITIONAL OPTIONS:

2MB Flash Memory (MM-15-2), 4MB Flash Memory (MM-15-4), 8MB Flash Memory (MM-15-8)
Telephone Handset (HS-40)

CONSUMABLES

TK-40	All-in-One Cartridge	9,000 pages@3% Coverage*
*based on ITU-T No. 1 chart in standard mode		
Ships with one TK-40 All-in-One Cartridge		



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.

Item Code# 87164139



www.kyoceramita.com