

KM-P4850w Specifications

BASIC SPECIFICATIONS:

| | |
|--------------------------|--|
| Configuration: | Wide Format Printer/Optional MFP with two 500' rolls, Single Sheet Bypass, Optional Network Scanning and Copying |
| Technology: | LED |
| Resolution: | 600 x 600 dpi. (16 bit) |
| Electrical Requirements: | 120V, 60Hz, 13A |
| Dimensions: | 52.4"W x 27.7"D x 43.1"H |
| Weight: | 524 lbs |

CADMaster Controller

BASIC SPECIFICATIONS:

| | |
|-----------------|---------------------------------|
| Platform: | Embedded Windows NT4.0 |
| Controller: | Duron CPU/800MHz |
| Printer Memory: | Standard 256MB RAM and 10GB HDD |
| Connectivity: | Standard 10/100 Base TX |

PRINT:

| | |
|---------------------------|---|
| File Formats: | HP-GL, HP-GL/2, HP-RTL, Calcomp 906/907, PCL, CALS-G4(TIFF 6.0), TIFF, BMP, JPEG, DXF, DWG with AutoCAD |
| Supported PDL/Emulations: | PostScript 2 Emulation |
| Windows OS Compatibility: | Windows 95/98/Me/2000/XP/NT4.0 |
| MAC OS Compatibility: | Mac OS 8.6/9.0/9.1 |
| Supported Protocols: | TCP/IP, AppleTalk |
| Drivers: | Windows, PPD for Mac, GDI, ADI/HDI for AutoCAD |
| Utilities: | Kyocera Mita Wide Format Web Manager (KMWWM), KM-Net Viewer, Print Utility with Tandem Print Capability |
| Other Print Functions: | lpr, ftp Printing |

OUTPUT SPEEDS:

| | |
|-------------------|---|
| Warm-Up Time: | Within 10 Minutes, Program and Scan During Warmup, Auto Start |
| Pages Per Minute: | 6 D Size Prints/minute |

PAPER SUPPLY:

| | |
|------------------------------|--|
| Standard Paper Sources: | 2 Rolls (Max. Capacity 500' per roll), Single Sheet Bypass, Auto Selection/Switching |
| Min./Max. Roll Widths: | 17"/36" |
| Min./Max. Bypass Paper Size: | 8.5" x 11"/36" x 48" |
| Total Paper Capacity: | 3-500' Rolls and Single Sheet Bypass |
| Paper Weight: | 20 - 24 lb. |
| Media Types: | Bond Paper, Film, Translucent Bond, Vellum |

OUTPUT:

| | |
|-------------------------|---|
| Output Size: | Width: 8.5" to 36", Length: 11" to 237" |
| Standard Drawing Sizes: | Architectural/ANSI/Metric |
| Output Tray Capacity: | 30 D Size |

PAPER HANDLING OPTIONS:

3RD ROLL UNIT: **RU-4A**

| | |
|-----------------------|--|
| Paper Capacity: | 500' Roll |
| Paper Weight: | 20 - 24 lb. |
| Min./Max. Roll Width: | 17"/36" |
| Media Types: | Bond Paper, Film, Translucent Bond, Vellum |

DOCUMENT SCANNER: KM-S4850w

| | |
|--------------------------------|---|
| Scanning Resolution/Grayscale: | 600 x 600 dpi/256 levels |
| Acceptable Originals: | Width: 8.5" to 36", Length: 11" to 237" |
| Scan Speed: | Up to 7 D's/minute |
| Capacity: | Single |
| Paper Weight: | 17 - 40 lb |
| Original Memory: | Standard 128MB, Upgradeable to 1GB |
| Standard Drawing Sizes: | Architectural/ANSI/Metric |

COPY FUNCTIONS:

| | |
|----------------------|--|
| Imaging Modes: | Normal, Text & Photo |
| Continuous Copy: | Up to 99 |
| Additional Features: | Auto Center, Auto Magnification and Paper Select, Rotate image, Margin Adjust, Image Move, Border Adjust, Mirror Image, Job Programming, Interrupt, Preview Copy, Repeat Copy, Sort/Group, Add Job |

NETWORK AND WEB SCANNING

| | |
|----------------------|--|
| Resolution: | 200, 300, 400, 600, 1,200, 2,400 1,200 dpi - Max Size is 18" x 24" fed portrait 2,400 dpi - Max. Size is 8.5" x 11" fed portrait |
| Scan Speed: | Up to 7 D's/minute (KM-P4850w) |
| File Formats: | Scan to PC: TIFF, JPEG Web Scanning: TIFF, JPEG, BMP |
| Connectivity: | Standard 10/100 Base TX |
| Supported Protocols: | TCP/IP, AppleTalk |
| Scanning Modes: | Scan to PC/File, Web Scanning/Scan to TWAIN Compliant Applications |
| Drivers: | TWAIN |
| Utilities: | KM Scanner File Utility, Kyocera Mita Wide Format Web Manager (KMWWM) |

ADDITIONAL OPTIONS:

| |
|---|
| Original Carry Sheet, Scanner Stand for KM-S4850w |
|---|

CONNECTIVITY OPTIONS:



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.

All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.

Item Code# XXXXXXXX



www.kyoceramita.com