

CS-2030 Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Digital Copier with Standard 250 x 2 Paper Drawers Plus 50 Sheet Multi-Purpose Tray, Optional Network Printing, Scanning and Fax.
Resolution:	600 x 600 DPI Resolution / 256 Levels, Fast 1200 DPI Print Resolution
Copier Memory:	Standard 64MB RAM
Magnification:	Full Size, Reduction, Enlargement, Plus 50-200% Zoom
Electrical Requirements:	120V, 60Hz, 9A
Dimensions:	22"W x 24"D x 22"H
Weight:	102 lbs
Max Monthly Volume:	30,000 Pages Per Month

OUTPUT SPEEDS:

Warm-Up Time:	Within 30 Seconds
First Copy Out:	5.5 Seconds
Pages Per Minute:	20 Letter, 11 Legal, 10 Ledger

PAPER SUPPLY:

Standard Paper Sources:	Dual 250 Sheet Drawers, 50 Sheet MPT, Auto Selection / Switching
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5 x 8.5 - 11" x 17"
Std / Max Paper Capacity:	550 / 1,050
Paper Weight:	17-21 lb Bond via Paper Drawers, 12 lb Bond - 88 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 250, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Book Mode, Combine Image, Erase Mode, Image Rotate, Interrupt, Margin Shift, 100 Management Codes

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: SRDF-1

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size
Capacity:	70 Sheet RADF / 20 Letter Size Originals Per Minute
Paper Weight:	9 42 lb Bond
Dimensions/Weight:	21.8 W x 18.8 D x 4.8 H / 23.1 lbs

DOCUMENT PROCESSOR: STDF-3

Type:	Sheet Through Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size
Capacity:	70 Sheet ADF / 20 Letter Size Originals Per Minute
Paper Weight:	9 42 lb Bond
Dimensions/Weight:	21.8 W x 18.8 D x 4.8 H / 15.2 lbs

DUPLEX UNIT/JOB SEPARATOR: AD-61

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17-21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1
Stack Capacity (Job Separator):	100 Sheets

DUPLEX UNIT FOR INTERNAL FINISHER: AD-62

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17-21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

INTERNAL FINISHER: F-2205

Stack Capacity:	500 Sheets
Paper Weight:	17 - 21 lb Bond
Staple Capacity:	30 Sheets: 8.5 x 11 ; 20 Sheets: 8.5 x 14 - 11 x 17
Edge Staple Position:	1 Position
Dimensions / Weight:	15.4 lbs

PAPER DRAWER: ST-12

Paper Capacity:	250 Sheets
Paper Weight:	17 - 21 lb Bond
Paper Size:	5.5 x 8.5 - 11 x 17
Dimensions / Weight:	21.6 W x 22.0 D x 4.5 H / 22 lbs

CONNECTIVITY OPTIONS:

PRINT: PRINT SYSTEM (K)

Controller:	Embedded PowerPC405 / 200 MHz Controller
Printer Memory:	Standard 8MB, Upgradeable to 136MB, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL2 (PS2)
Fonts:	80 Outline Fonts for PCL/KPDL, 1 Bitmap Font
Windows OS Compatibility:	Windows 95/98/Me/NT4.x/2000/XP
Novell OS Compatibility:	Novell NetWare 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard Parallel IEEE1284,
KUIO LV Expansion Slot (1):	Optional IB-21 10/100BaseTX, IB-20 10/100BaseTX; 10Base2; Optional IB-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, Network Advanced Setup Utilities, PRESCRIBE Utilities

SCANNING: Scan System (A)

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 10 Sheets Per Minute
File Formats:	PDF, TIFF
Connectivity:	Standard NS-20 10/100BaseTX, 10Base2
Supported Protocols:	TCP/IP
Scanning Features:	Scan to PC/File, Scan to E-Mail, TWAIN
Driver:	TWAIN Driver
Utilities:	KM Scanner File Utility, Scanner Delivery Utility, Network Advanced Setup Utilities

FAX: Fax System (B)

Compatibility:	G3
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Std 8MB / Max 16MB
Additional Features:	Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2 in 1 RX

ADDITIONAL OPTIONS:

Job Separator (J-1302), 8MB Fax Memory Board (FM1-8MB), Stand



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.



www.copystar.com