

# Ri-4030 Specifications

## BASIC SPECIFICATIONS:

Configuration:	Desktop Digital Copier with Standard 500 x 2 Paper Drawers Plus 200 Sheet Multi-Purpose Tray, Optional Network Printing, Scanning and Network Fax.
Resolution:	600 x 600 DPI Resolution / 256 Levels, Fast 1200 DPI Print Resolution
Copier Memory:	Standard 32MB RAM, upgradeable to 160MB
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom
Electrical Requirements:	120V, 60Hz, 12A
Dimensions:	23"W x 25"D x 29"H
Weight:	165 lbs
Max Monthly Volume:	150,000 Pages Per Month

## OUTPUT SPEEDS:

Warm-Up Time:	Within 60 Seconds, Program During Warmup, Auto Start
First Copy Out:	3.9 Seconds
Pages Per Minute:	40 Letter, 23 Legal, 19 Ledger

## PAPER SUPPLY:

Standard Paper Sources:	Dual 500 Sheet Drawers, 200 Sheet MPT, Auto Selection / Switching, Add Paper While Running
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	1,200 / 4,200
Paper Weight:	16-28 lb Bond via Paper Drawers, 16 lb Bond -110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

## COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Batch Copy, Booklet Mode, Book Mode, Combine Image, Covers, Erase Mode, Image Overlay, Image Rotate, Image Reverse, Interrupt, 8 Job Programs, Margin Shift, Mirror Image, Page Numbering, Transparency Mode, 500 Management Codes, XY Zoom

## PAPER HANDLING OPTIONS:

### OPTIONAL DOCUMENT PROCESSOR: SRDF-2

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Processing
Capacity:	100 Sheet RADF / 40 Letter Size Originals Per Minute
Paper Weight:	9-42 lb Bond
Dimensions / Weight:	21.8"W x 18.8"D x 5.4"H / 23 lbs

### OPTIONAL DUPLEX UNIT: AD-63

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17 - 21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

### FINISHER: DF-71

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray: 250 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 11" x 17"
Paper Weight:	12 lb Bond - 110 lb Index
Staple Capacity:	50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	3 Positions: Top Left, Bottom Left, Left/Top Side
Punch:	Standard 2 and 3 Hole
Dimensions / Weight:	27.1"W x 23.5"D x 41.5"H / 110 lbs

### SADDLE STITCH FINISHER: DF-75

Stack Capacity:	Main Tray: 1,000 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"
Paper Weight:	16 lb Bond - 110 lb Index
Staple Capacity:	50 Sheets: 8.5" x 11"; 25 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	4 Positions: Top Left, Bottom Left, Left Side, Center
Saddle Stitch:	8.5" x 11", 11" x 17"; Up to 10 Sheets
Punch:	Optional 2 and 3 Hole
Dimensions / Weight:	28.3"W x 23.7"D x 39.4"H / 86 lbs

### INTERNAL FINISHER: DF-78

Stack Capacity:	500 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14" - 11" x 17"
Edge Staple Position:	1 Position
Dimensions/Weight:	12.2"W x 16.0"D x 6.3" H 19.8 lbs

## MULTI-BIN MAILBOX: M-2107

Number of Trays:	7
Tray Capacity:	100 Sheets: 5.5" x 8.5" - 8.5" x 11"; 50 Sheets: 8.5" x 14" - 11" x 17"
Paper Weight:	17 - 21 lb Bond
Dimensions / Weight:	20.0"W x 15.7"D x 18.5"H / 22 lbs

## PUNCH UNIT: PH-2

Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	17 lb Bond - 110 lb Index
Number of Holes:	2 and 3
Weight:	5.2 lbs

## LARGE CAPACITY TRAY: PF-75

Paper Capacity:	3,000 Sheets
Paper Weight:	16 - 28 lb Index
Paper Size:	8.5" x 11"
Dimensions / Weight:	23.2"W x 12.4"D x 23"H / 48 lbs

## DUAL PAPER DRAWERS: PF-70

Paper Capacity:	2 x 500 Sheets
Paper Weight:	16 - 28 lb Index
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	23.2"W x 12.4"D x 23"H / 57.4 lbs

## CONNECTIVITY OPTIONS:

### PRINT/SCAN: PRINT/SCAN SYSTEM (N)

Controller:	Embedded PowerPC750 / 350 MHz Controller
Printer Memory:	Standard 32MB, Upgradeable to 288MB via 100 Pin DIMMS, Optional Printer HDD, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, Parallel IEEE1284, Serial RS-232C
KUIO LV Expansion Slots (2):	Optional Printer Hard Disk Drive Optional IB-22 Enhanced Wireless NIC; IB-20 10/100BaseTX, 10Base2
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

### SCAN:

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 40 Sheets Per Minute
File Formats:	PDF, TIFF
Connectivity:	Standard NS-30 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	KM Document Flow System - Document Management System, Scan to PC/File, Scan to Mac, Scan to E-Mail, TWAIN
Driver:	TWAIN Driver
Utilities:	KM DB-Assistant, KM Scanner File Utility, Scan to Mac Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities

### PRINTER HARD DISK DRIVE:

Enables Document Printing and e-MPS Functions; Private Print, Job Storage, Quick Copy, Proof & Hold, Virtual MailBoxes, Bar Code

### FAX/NETWORK FAX: Fax System (F)

Compatibility:	Super G3
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Std 8MB / Max 16MB
Driver:	KM Network Fax Driver
Utilities:	Address Book for NW Fax
Additional Features:	Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2 in 1 RX,

## ADDITIONAL OPTIONS:

Job Separator (J-1402), Bar Code Reader (BC-1), 8MB Fax Memory Board (FM1-8MB), Stand



Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).  
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA

©2003 Kyocera Mita America, Inc.

Item Code# 87164139



[www.copystar.com](http://www.copystar.com)