



Serious Business.

Serious **Color.**

- 26 ppm Color/B&W
- Standard Print/Copy/Scan Controller
- Optional Fax and Network Fax
- Two flexible product configurations with 3,150 or 1,650-sheet paper supply
- Advanced finishing options including multi-position stapling, folding, booklet making and hole punching
- Long life consumables: 300K Drum and Maintenance Kits
- Standard 512MB RAM; 20GB HDD

KM-G2630D
COLOR DOCUMENT IMAGING SOLUTION

 **KYOCERA**
Document Solutions

KM-C2630D-A / KM-C2630D-B Specifications

BASIC SPECIFICATIONS:

Configuration:	Digital Color Copier/Printer/Scanner with Standard Duplex, 150 Sheet Multi-Purpose Tray (MPT), and Optional Finishing. Type A: 3,000 Sheets (500/1,000/1,500) Type B: 1,500 Sheets (500 x 3) Optional Fax/Network Fax
Resolution:	Multi-bit 600 x 600 DPI
Copier Memory:	Standard 512MB RAM, 20GB Hard Disk Drive
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom
Electrical Requirements:	120V, 60Hz, 12.5A
Dimensions:	Type A and B: 27.5"W x 31.7"D x 61.2"H
Weight:	Type A: 299.3 lbs Type B: 277.3 lbs
Max Monthly Volume:	70K B/W; 30K Color Pages Per Month

OUTPUT SPEEDS:

Warm-Up Time:	Less than 179 Seconds
First Copy Out (Color/Mono):	9.4 Seconds or less
First Print Out (Color/Mono):	9.0 Seconds or less
Pages Per Minute (Color/Mono):	26/26 Letter, 13/13 Legal, 11/11 Ledger
Continuous Copy:	Up to 999, Auto Reset to 1

IMAGE QUALITY AND VERSATILITY:

Imaging Modes:	Text, Photo, Text/Photo, Print, Map
Additional Features:	Auto Cassette Selection, Auto Paper Selection, Auto Magnification Selection, Auto Exposure Selection, 1,000 Account Codes, Rotate Copy, Electronic Sort, Rotate Sort, Booklet Copy, N-up Copy, Page Numbering, Cover, Insert, Chapter, OHP Interleaving, Margin Shift, Border Erase, Invert, Mirror, Page Separation
Color Adjustments:	Auto Color Selection, Mono Color Copy, Quick Image, Color Balance, Hue, Sharpness, Low or High Gloss Mode, Color Calibration

PAPER SUPPLY:

Standard Paper Sources:	Type A: 3,000-sheets (500/1,000/1,500) with 150-sheet MPT Type B: 1,500-sheets (500 x 3) with 150-sheet MPT
Drawer Paper Size (Min/Max):	5.5" x 8.5" - 11" x 17"
MPT Paper Size (Min/Max):	2.5" x 5.5" - 12" x 18"
Paper Capacity:	Type A: 3,150-sheets Type B: 1,650-sheets
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

DUPLEX UNIT:

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: SRDF-2

Type:	Reversing Automatic Document Processor (RADF)
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Processing
Capacity:	100 Sheet RADF
Paper Weight:	9 - 42 lb Bond
Dimensions/Weight:	21.8"W x 18.8"D x 5.4"H/23 lbs

MULTI-FUNCTIONAL FINISHER: DF-610

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray: 200 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 11" x 17"
Paper Weight:	Main: 16 lb Bond - 90 lb Index; Sub: 16 lb Bond - 110 lb Index
Staple Capacity:	50 Sheets: 5.5" x 8.5", 8.5" x 14", 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	4 Positions: Top Left, Bottom Left, Two Left, Two Center
Saddle Stitch:	8.5" x 11", 11" x 17"; Up to 16 Sheets
Dimensions/Weight:	31.4"W x 25.2"D x 37.4"H/172 lbs

MULTI TRAY: MT-1

Number of Trays:	5
Capacity:	150 Sheets (8.5" x 11") Per Tray
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	13 lb Bond - 90 lb Index
Dimensions/Weight:	14.5"W x 15.5"D x 22.6"H/33 lbs

BOOKLET FOLDER: BF-1

Folding Capacity:	1 - 16 Sheets
Capacity:	1 - 5 Sheets - 40 Booklets 6 - 10 Sheets - 24 Booklets 11 - 16 Sheets - 15 Booklets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 lb Bond - 110 lb Index, Over 20 lb is one sheet only
Dimensions/Weight:	23.3"W x 17"D x 10"H/42 lbs

PUNCH UNIT: PH-3

Paper Size:	8.5" x 11" - 11" x 17"
Number of Holes:	2 and 3
Weight:	8 lbs

STANDARD CONNECTIVITY:

PRINT:

Controller:	Embedded PowerPC750Cxe/600 MHz Controller
Printer Memory:	Standard 256MB, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, KPDL3 (PS3), PCL6 (PCL XL, PCL 5e), KGGL (HP-GL/2),
Fonts:	136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/5e/XL, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, Bi-Directional Parallel IEEE1284 Optional IB-11 Serial RS-232C; IB-20 10/100BaseTX, 10Base2; IB-22 Enhanced Wireless NIC;
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver
Utilities:	KM-NET Viewer, PDF Direct Print, KM-NET for Clients, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

SCAN:

Resolution:	200, 300, 400, 600 DPI
Color Mode:	Auto Color, Full Color, Grayscale, Black
Color/Mono Scan Speed:	Up to 21/31 Original per Minute
File Formats:	PDF, TIFF, JPEG
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	KM Document Flow System - Document Management System, Scan to PC/File, Scan to Mac, Scan to E-Mail, TWAIN
Driver:	TWAIN
Utilities:	KM DB-Assistant, KM Scanner File Utility, Scan to Mac Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities

CONNECTIVITY OPTION:

FAX/NETWORK FAX: FAX SYSTEM (H)

Compatibility:	Super G3
Transmission Speed:	Approximately 3 Second per Page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Std./Max Memory:	8MB/16MB
Fax Features:	Duplex TX/RX, Confidential TX/RX, Polling, Broadcasting
Utilities:	Address Book for NW Fax
Driver:	KM Network Fax Driver

ADDITIONAL OPTIONS:

500 Sheet Face Up Tray (PT-640); 32, 64, 128, 256MB DIMM for Printer
--



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2005 Kyocera Mita America, Inc.
IC# 87166670



www.kyoceramita.com