

# KM-P4845W Specifications

## BASIC SPECIFICATIONS:

Configuration:	Wide Format Printer/Optional MFP with two 500' rolls, Single Sheet Bypass, Optional Network Scanning and Copying
Technology:	LED
Resolution:	600 x 600 dpi. (16 bit)
Electrical Requirements:	120V, 60Hz, 13A
Dimensions:	52.4"W x 27.7"D x 43.1"H
Weight:	524 lbs

## CADMaster Controller

### BASIC SPECIFICATIONS:

Platform:	Embedded Windows NT4.0
Controller:	Duron CPU/800MHz
Printer Memory:	Standard 128MB RAM and 10GB HDD
Connectivity:	Standard 10/100 Base TX

### PRINT:

File Formats:	HP-GL, HP-GL/2, HP-RTL, Calcomp 906/907, PCL, CALS-G4(TIFF 6.0), TIFF, BMP, JPEG, DXF, DWG with AutoCAD
Supported PDL/Emulations:	PostScript 2 Emulation
Windows OS Compatibility:	Windows 95/98/Me/2000/XP/NT4.0
MAC OS Compatibility:	Mac OS 8.6/9.0/9.1
Supported Protocols:	TCP/IP, AppleTalk
Drivers:	Windows, PPD for Mac, GDI, ADI/HDI for AutoCAD
Utilities:	Kyocera Mita Wide Format Web Manager (KMWWM), KM-Net Viewer, Print Utility with Tandem Print Capability
Other Print Functions:	lpr, ftp Printing

### OUTPUT SPEEDS:

Warm-Up Time:	Within 10 Minutes, Program and Scan During Warmup, Auto Start
Pages Per Minute:	4 D Size Prints/minute

### PAPER SUPPLY:

Standard Paper Sources:	2 Rolls (Max. Capacity 500' per roll), Single Sheet Bypass, Auto Selection/Switching
Min./Max. Roll Widths:	17"/36"
Min./Max. Bypass Paper Size:	8.5" x 11"/36" x 48"
Total Paper Capacity:	3-500' Rolls and Single Sheet Bypass
Paper Weight:	20 - 24 lb.
Media Types:	Bond Paper, Film, Translucent Bond, Vellum

### OUTPUT:

Output Size:	Width: 8.5" to 36", Length: 11" to 237"
Standard Drawing Sizes:	Architectural/ANSI/Metric
Output Tray Capacity:	30 D Size

### PAPER HANDLING OPTIONS:

#### 3RD ROLL UNIT: **RU-4A**

Paper Capacity:	500' Roll
Paper Weight:	20 - 24 lb.
Min./Max. Roll Width:	17"/36"
Media Types:	Bond Paper, Film, Translucent Bond, Vellum

### CONNECTIVITY OPTIONS:

## DOCUMENT SCANNER: KM-S4850w

Scanning Resolution/Grayscale:	600 x 600 dpi/256 levels
Acceptable Originals:	Width: 8.5" to 36", Length: 11" to 237"
Scan Speed:	Up to 7 D's/minute
Capacity:	Single
Paper Weight:	17 - 40 lb
Original Memory:	Standard 128MB, Upgradeable to 1GB
Standard Drawing Sizes:	Architectural/ANSI/Metric

### COPY FUNCTIONS:

Imaging Modes:	Normal, Text & Photo
Continuous Copy:	Up to 99
Additional Features:	Auto Center, Auto Magnification and Paper Select, Rotate image, Margin Adjust, Image Move, Border Adjust, Mirror Image, Job Programming, Interrupt, Preview Copy, Repeat Copy, Sort/Group, Add Job

### NETWORK AND WEB SCANNING

Resolution:	200, 300, 400, 600, 1,200, 2,400 1,200 dpi - Max Size is 18" x 24" fed portrait 2,400 dpi - Max. Size is 8.5" x 11" fed portrait
Scan Speed:	Up to 7 D's/minute (KM-P4850w)
File Formats:	Scan to PC: TIFF, JPEG Web Scanning: TIFF, JPEG, BMP
Connectivity:	Standard 10/100 Base TX
Supported Protocols:	TCP/IP, AppleTalk
Scanning Modes:	Scan to PC/File, Web Scanning/Scan to TWAIN Compliant Applications
Drivers:	TWAIN
Utilities:	KM Scanner File Utility, Kyocera Mita Wide Format Web Manager (KMWWM)

### ADDITIONAL OPTIONS:

Original Carry Sheet, Scanner Stand for KM-S4850w
---



Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).

All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA  
©2003 Kyocera Mita America, Inc.

Item Code# XXXXXXXX



[www.kyoceramita.com](http://www.kyoceramita.com)