

# CS-1810 Specifications

## BASIC SPECIFICATIONS:

Configuration:	Desktop Digital Copier with Standard 250 Sheet Paper Drawer Plus 50 Sheet Multi-Purpose Tray, Optional Network Printing
Resolution:	600 x 600 DPI Resolution / 256 Levels, Fast 1200 DPI Print Resolution
Copier Memory:	Standard 16MB RAM
Magnification:	Full Size, 2 Reduction, 2 Enlargement Preset Ratios, Plus 50-200% Zoom
Electrical Requirements:	120V, 60Hz, 12A
Dimensions:	20"W x 20"D x 18"H
Weight:	59.5 lbs
Max Monthly Volume:	15,000 Pages Per Month

## OUTPUT SPEEDS:

Warm-Up Time:	Within 30 Seconds
First Copy Out:	6.3 Seconds
Pages Per Minute:	18 Letter, 15 Legal

## PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer, 50 Sheet MPT, Auto Selection / Switching with optional paper drawer
Drawer Paper Size:	5.5" x 8.5" - 8.5 x 14
MPT Paper Size:	5.5 x 8.5 - 8.5 x 14
Std / Max Paper Capacity:	300 / 550
Paper Weight:	17-21 lb Bond via Paper Drawers, 16 lb Bond -88 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

## DOCUMENT PROCESSOR:

Type:	Sheet Through Document Feeder
Acceptable Originals:	5.5" x 8.5" - 8.5 x 14
Capacity:	30 Sheet SADP / 15 Letter Size Originals per Minute
Paper Weight:	13 - 32 lb Bond

## COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 99, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Scan Once Print Many, Electronic Sort, 2 in 1, 4 in 1, ECO Mode

## PAPER HANDLING OPTIONS:

### PAPER DRAWER: ST-13

Paper Capacity:	250 Sheets
Paper Weight:	17 - 21 lb Bond
Paper Size:	5.5 x 8.5 - 8.5 x 14
Dimensions / Weight:	19.6 W x 19.1 D x 3.5 H / 11.0 lbs

## CONNECTIVITY OPTION:

### PRINT: PRINT SYSTEM (M)

Controller:	Embedded PowerPC405 / 200 MHz Controller
Printer Memory:	Standard 8MB, Upgradeable to 136MB, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL2 (PS2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Lineprinter
Fonts:	80 Outline Fonts for PCL/KPDL, 1 Bitmap Font
Windows OS Compatibility:	Windows 95/98/Me/NT4.x/2000/XP
Novell OS Compatibility:	Novell NetWare 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard Parallel IEEE1284
KUIO LV Expansion Slot (1):	Optional 1B-21 10/100BaseTX, 1B-20 10/100BaseTX, 10Base2; Optional 1B-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

## ADDITIONAL OPTIONS:

Stand	
-------	--



Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).  
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA  
©2003 Kyocera Mita America, Inc.



Kyocera Mita, Inc. 2003-1-0001  
Certified for Environmental  
Management

[www.copystar.com](http://www.copystar.com)