

CS-1530 Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Digital Copier with Standard 250 Sheet Paper Drawer Plus 50 Sheet Multi-Purpose Tray, Optional Network Printing
Resolution:	600 x 600 DPI Resolution / 256 Levels, Fast 1200 DPI Print Resolution
Copier Memory:	Optional 32MB or 64MB RAM
Magnification:	Full Size, Reduction, Enlargement, Plus 50-200% Zoom
Electrical Requirements:	120V, 60Hz, 9A
Dimensions:	22"W x 22"D x 18"H
Weight:	86 lbs
Max Monthly Volume:	15,000 Pages Per Month

OUTPUT SPEEDS:

Warm-Up Time:	Within 30 Seconds
First Copy Out:	5.5 Seconds
Pages Per Minute:	w/o Memory Board: 15 Letter, 8 Legal, 8 Ledger w/ Memory Board: 18 Letter, 10 Legal, 9 Ledger

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer, 50 Sheet MPT, Auto Selection / Switching
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5 x 8.5 - 11" x 17"
Std / Max Paper Capacity:	300 / 1,050
Paper Weight:	17-21 lb Bond via Paper Drawers, 12 lb Bond -88 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 250, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Book Mode, Combine Image, Erase Mode, Image Rotate, Interrupt, Margin Shift, 100 Management Codes

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: STDF-3

Type:	Sheet Through Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size
Capacity:	70 Sheet ADF / 15 Letter Size Originals Per Minute
Paper Weight:	9 - 42 lb Bond
Dimensions/Weight:	21.8 W x 18.8 D x 4.8 H / 15.2 lbs

PAPER DRAWER: ST-12

Paper Capacity:	250 Sheets
Paper Weight:	17 - 21 lb Bond
Paper Size:	5.5 x 8.5 - 11 x 17
Dimensions / Weight:	21.6 W x 22.0 D x 4.5 H / 22 lbs

CONNECTIVITY OPTIONS:

PRINT: PRINT SYSTEM (K)

Controller:	Embedded PowerPC405 / 200 MHz Controller
Printer Memory:	Standard 8MB, Upgradeable to 136MB, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL2 (PS2)
Fonts:	80 Outline Fonts
Windows OS Compatibility:	Windows 95/98/Me/NT4.x/2000/XP
Novell OS Compatibility:	Novell NetWare 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard Parallel IEEE1284
KUIO LV Expansion Slot (1):	Optional 1B-21 10/100BaseTX, 1B-20 10/100BaseTX, 10Base2; Optional 1B-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, Network Advanced Setup Utilities, PRESCRIBE Utilities

ADDITIONAL OPTIONS:

Job Separator (J-1302), 32MB Copy Memory Board(MB-5A), 64MB Copy Memory Board(MB-5), Stand



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA

©2003 Kyocera Mita America, Inc.



www.copystar.com